

Salsa

2025

WOOD
product
data
sheet



Salsa, the most diversified wood flooring collection, brings the power of nature to living space. Wood species from all over the world, designs and various surface effects are carefully designed to rediscover charms of emotions and little secrets of life!

board size: 2283 x 194 x 14 mm

product line/ subline	code	product name	wood specie	grade	digital print	stain	surface lacquer	gloss level	brushed	bevel	dop number
Essential Pure / White	550049124	OAK ICEBERG	Oak	Original	No	No	PN(M)	9	Yes	No	2702-00020-DoP-2024-01
Essential Classic / Nature	550049126	OAK ELEGANT MATT	Oak	Elegant	No	No	PN(M)	9	Yes	No	2702-00020-DoP-2024-01
Essential Classic / Nature	550049127	OAK ELEGANT SHINY	Oak	Elegant	No	No	PL(S)	30	Yes	No	2702-00020-DoP-2024-01
Essential Classic / Nature	550049128	OAK VIVID	Oak	Vivid	No	No	PN(M)	9	Yes	No	2702-00020-DoP-2024-01
Essential Classic / Nature	550049129	OAK ELEGANT HIGH GLOSS	Oak	Elegant	No	No	PL (HG)	70	Yes	No	2702-00020-DoP-2024-01
Essential Classic / Beige	550049130	OAK ROBUST WHITE	Oak	Original	No	Yes	PL(S)	30	Yes	No	2702-00020-DoP-2024-01
Essential Brown / Cocoa	550049131	OAK CHOCOLATE	Oak	Original	No	Yes	PN(M)	9	Yes	No	2702-00020-DoP-2024-01
Essential Pure / Antique White / Grey	550049132	OAK NORDIC ELEGANT	Oak	Elegant	No	Yes	PL(S)	30	No	No	2702-00020-DoP-2024-01
Essential Brown / Cocoa	550049133	OAK COCOA	Oak	Vivid	No	Yes	PN(M)	9	Yes	No	2702-00020-DoP-2024-01
Essential Pure / White	550049139	ASH SILKY WHITE	Ash	Nature	Yes	No	PL(S)	30	Yes	No	2702-00020-DoP-2024-01
Essential Pure / White	550049140	OAK COTTON	Oak	Vivid	No	Yes	PN(M)	9	Yes	No	2702-00020-DoP-2024-01
Essential Classic / Nature	550049142	OAK SUPREME MATT	Oak	Supreme	No	No	PN(M)	9	Yes	No	2702-00020-DoP-2024-01
Essential Classic / Beige	550049143	OAK LINEN	Oak	Vivid	No	Yes	PN(M)	9	Yes	No	2702-00020-DoP-2024-01
Essential Brown / Mocha	550049145	OAK SIENNA	Oak	Vivid	No	Yes	PN(M)	9	Yes	No	2702-00020-DoP-2024-01
Essential Classic / Nature	550049152	OAK ORIGINAL MATT	Oak	Original	No	No	PN(M)	9	Yes	No	2702-00020-DoP-2024-01
Essential Classic / Nature	550049153	OAK ORIGINAL SHINY	Oak	Original	No	No	PL(S)	30	Yes	No	2702-00020-DoP-2024-01
Essential Classic / Nature	550049154	OAK ORIGINAL HIGH GLOSS	Oak	Original	No	No	PL (HG)	70	Yes	No	2702-00020-DoP-2024-01
Essential Brown / Mocha	550049156	OAK COPPER ORIGINAL	Oak	Original	No	Yes	PN(M)	9	Yes	No	2702-00020-DoP-2024-01

PL(S) – Proteco Lacquer Shiny PN(M) – Proteco Nature Matt PL(HG) – Proteco Lacquer High Gloss

installation

- Floating or glue down installation.
- Surface must be clean, dry and flat.
- Relative air humidity: 30-60%.
- Room temperature: 18-27°C.



T-LOCK
Tarkett lock, glue-free locking system

AQUA GUARD
Extended liquid resistance at the short side of boards connection

HEALTHY FLOORS
Lacquer properties prevent bacteria reproduction

ENVIRONMENTAL COMMITMENT
Environmental responsibility throughout all processes (C2C, FSC, ISO14001)

WARRANTY
30 years residential warranty

maintenance

- The finishing technology used for Tarkett floors makes them the best choice for easy maintenance. To preserve all the beauty of your Tarkett wood flooring, simply follow simple protection suggestions.

- 1— **WET MOPPING OR VACCUMING:** Wet mopping with almost dry cloth.
Use protective pads when moving furniture
- 2— **DRY CLEANING:** Dry mopping & vaccum cleaning
- 3— **REGULAR CLEANING:** Tarkett Cleaner
- 4— **PERIODICAL CLEANING:** Tarkett Refresher



underfloor heating

- Since wood is a living material, during the heating season, minor gaps might develop between wood flooring boards due to interior climate conditions. These gaps cannot be related to product quality. Boards movement can be minimized by keeping temperature level at approx. 20° C and a relative air humidity at approx. 50 %.
- *Not suitable for the wood species beech and maple

technical data

product description: Multilayer 14 mm parquet with surface coating for indoor use (EN 13489)

essential characteristics	performance	harmonised technical specification
A – Reaction to fire	Dfl-s1	EN 14342:2013
the minimum mean density	500 kg/m ³	
the minimum overall thickness	14 mm	
the end-use condition to be applied	glued to the substrate or with or without air gap underneath	
B – Formaldehyde emission	E1	
C – Content of pentachlorophenol	< 5 ppm	
D – Breaking strength	NPD	
E – Slip resistance	NPD	
G – Thermal conductivity	0,10 W/m K	
H – Biological durability	Class 1	

size and package

size and package characteristics	value
Thickness (mm)	~14
Width (mm)	194
Length (mm)	2283
Wear layer thickness (mm)	~2,8
Boards/package	6
m ² /pack	2,658
m ² /pallet	132,9
Weight/m ² (kg)	~7,24

design overview



OAK ICEBERG BR



OAK ELEGANT MATT



OAK ELEGANT SHINY



OAK VIVID



OAK ELEGANT HIGH GLOSS



OAK ROBUST WHITE BR



OAK CHOCOLATE BR



OAK NORDIC ELEGANT



OAK COCOA



ASH SILKY WHITE BR



OAK COTTON BR



OAK SUPREME MATT



OAK LINEN BR



OAK SIENNA



OAK ORIGINAL MATT



OAK ORIGINAL SHINY



OAK ORIGINAL HIGH GLOSS



OAK COPPER ORIGINAL